

POWER WEEDER

BUILT FOR INTENSE OPERATION



VST FT 50 GE



Strong Cast Iron
Gearbox



Mud Protective
Fender



Adjustable Handle



Assurance of
Service & Spare Parts

APPLICATIONS: Puddling, Intercultivation, Weeding, Bund Formation, Spraying etc.

SUITABLE FOR: Vegetable Crops, Horticulture & Plantation Crops



1800 419 0136



info@vsttractors.com



www.vsttractors.com



TECHNICAL SPECIFICATIONS

PRODUCT DETAILS	Category	Power Weeder
	Model	VST FT 50 GE
	Type	Front Rotary
ENGINE	Type	Four Stroke, Single Cylinder, Inclined, Air Cooled, Spark Ignition, Petrol Engine
	Bore × Stroke, mm	70 × 55
	Displacement, cc	212
	Max. Power, kW(HP) @ RPM	4.0 (5.4) @3600
	Starting System	Recoil (Manual)
TRANSMISSION	Transmission Drive	Gear Drive
	No. of Speeds	03 (02- Forward & 01- Reverse)
	Wheels Type & Nos.	Pneumatic, Traction & 2 Nos.
	Wheels Size	4.00 - 8, 2 PR
ROTARY	No. of Blades	24
	Rotary Speed	2
	Avg. Width of Cut, mm	1050 - 1100
	Avg. Depth of Cut, mm	64 - 70
PRODUCT OVERALL	Overall Dimension (L × W × H), mm	1440 × 1090 × 1000/1370
	Gross Weight, Kg	79

COMPATIBLE ATTACHMENTS



Ridger



Sprayer



Cultivator



Potato Harvester



Trailer



VST TILLERS
TRACTORS LTD.

Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road,
Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91 - 80 - 67141111, e-mail: tollfree@vsttractors.com,
CIN: L34101KA1967PLC001706. www.vsttractors.com

Authorized Dealer

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice. Performance of the machine may vary with user/field/working conditions.



1800 419 0136

[f /vsttillers](https://www.facebook.com/vsttillers)

[in /company/vst-tillers](https://www.linkedin.com/company/vst-tillers)

<http://bit.ly/VSTVideos>